

In Re Patent Application of:  
**TEGGE, JR. ET AL.**  
Serial No. 10/673,869  
Filing Date: **SEPTEMBER 29, 2003**

---

**In the Claims:**

This listing of claims replaces all prior versions and listing of claims in the application.

1. (Currently amended) A free space optical (FSO) communications device comprising:

a plurality of power supplies having different respective output voltages;

an adaptive optics (AO) module comprising an AO housing and a deformable mirror carried thereby, said deformable mirror comprising an array of actuators each operating based upon a supplied voltage; and

a power controller for determining a lowest one of the output voltages that will cause said deformable mirror to correct a given optical wavefront distortion, and selectively driving said array of actuators using a desired one of said power supplies said power supply providing the determined lowest output voltage to conserve electrical power.

2. (Original) The FSO communications device of Claim 1 wherein said deformable mirror further comprises a reflective deformable member mounted on said array of actuators.

3. (Original) The FSO communications device of Claim 1 wherein said AO module further comprises a thermal stress

In Re Patent Application of:  
**TEGGE, JR. ET AL.**  
Serial No. 10/673,869  
Filing Date: **SEPTEMBER 29, 2003**

---

isolation mount connecting said deformable mirror to said AO housing.

4. (Original) The FSO communications device of Claim 1 further comprising an interchangeable optical relay (OR) module comprising an OR housing and at least one OR device carried thereby, said OR housing and said AO housing being interchangeably connectable and establishing an optical path between said at least one OR device and said deformable mirror when connected.

5. (Original) The FSO communications device of Claim 4 wherein said at least one OR device of a given OR module provides a predetermined focal length range from among different focal length ranges for respective OR modules.

6. (Original) The FSO communications device of Claim 4 wherein said at least one OR device comprises a fixed telescopic lens device.

7. (Currently amended) The FSO communications device of Claim 4 further comprising a base module connected to said AO module for providing relative movement between said base module and said OR module for optical beam aiming.

In Re Patent Application of:  
**TEGGE, JR. ET AL.**  
Serial No. 10/673,869  
Filing Date: **SEPTEMBER 29, 2003**

---

8. (Original) The FSO communications device of Claim 7 wherein said base module comprises a base housing and at least one positioner carried thereby.

9. (Original) The FSO communications device of Claim 8 wherein said base module further comprises a controller for controlling said at least one positioner and a remote station interface connected to said controller for permitting remote control of said at least one positioner.

10. (Currently amended) A free space optical (FSO) communications system comprising:

first and second FSO communications devices aligned for optical communication therebetween, each comprising

a plurality of power supplies having different respective output voltages,

an adaptive optics (AO) module comprising an AO housing and a deformable mirror carried thereby, said deformable mirror comprising an array of actuators each operating based upon a supplied voltage, and

a power controller for determining a lowest one of the output voltages that will cause said deformable mirror to correct a given optical wavefront distortion, and selectively driving said array of actuators using a desired one of said power supplies said power supply

In Re Patent Application of:  
**TEGGE, JR. ET AL.**  
Serial No. 10/673,869  
Filing Date: **SEPTEMBER 29, 2003**

---

providing the determined lowest output voltage to  
conserve electrical power.

11. (Original) The FSO communications system of Claim 10 wherein said deformable mirror further comprises a reflective deformable member mounted on said array of actuators.

12. (Original) The FSO communications system of Claim 10 wherein said AO module further comprises a thermal stress isolation mount connecting said deformable mirror to said AO housing.

13. (Original) The FSO communications system of Claim 10 wherein each of said first and second FSO communications devices further comprises an interchangeable optical relay (OR) module comprising an OR housing and at least one OR device carried thereby, each OR housing and respective AO housing being interchangeably connectable and establishing an optical path between said at least one OR device and said deformable mirror thereof when connected.

14. (Original) The FSO communications system of Claim 13 wherein said at least one OR device of a given OR module provides a predetermined focal length range from among different focal length ranges for respective OR modules.

In Re Patent Application of:  
**TEGGE, JR. ET AL.**  
Serial No. **10/673,869**  
Filing Date: **SEPTEMBER 29, 2003**

---

15. (Original) The FSO communications system of Claim 13 wherein said at least one OR device comprises a fixed telescopic lens device.

16. (Currently amended) The FSO communications system of Claim ~~10~~ 13 wherein each of said first and second FSO devices further comprises a base module connected to said AO module for providing relative movement between said base module and said OR module for optical beam aiming.

17. (Original) The FSO communications system of Claim 16 wherein each base module comprises a base housing and at least one positioner carried thereby.

18. (Original) The FSO communications system of Claim 17 wherein each base module further comprises a controller for controlling said at least one positioner and a remote station interface connected to said controller for permitting remote control of said at least one positioner.

19. (Currently amended) A power conservation method for a free space optical (FSO) communications device comprising an adaptive optics (AO) module comprising an AO housing and a deformable mirror carried thereby, the deformable mirror comprising an array of actuators each operating based upon a supplied voltage, the method comprising:

In Re Patent Application of:  
**TEGGE, JR. ET AL.**  
Serial No. 10/673,869  
Filing Date: **SEPTEMBER 29, 2003**

---

providing a plurality of power supplies having  
different respective output voltages;

determining a lowest one of the output voltages that  
will cause the deformable mirror to correct a given optical  
wavefront distortion; and

selectively driving the array of actuators using a  
~~desired one of the power supplies~~ the power supply providing the  
determined lowest output voltage to conserve electrical power.

20. (Original) The method of Claim 19 wherein the  
deformable mirror further comprises a reflective deformable  
member mounted on the array of actuators.

21. (Original) The method of Claim 19 wherein the AO  
module further comprises a thermal stress isolation mount  
connecting the deformable mirror to the AO housing.

22. (Original) The method of Claim 19 wherein the FSO  
communications device further comprises an interchangeable  
optical relay (OR) module comprising an OR housing and at least  
one OR device carried thereby, the OR housing and the AO housing  
being interchangeably connectable and establishing an optical  
path between the at least one OR device and the deformable mirror  
when connected.

In Re Patent Application of:  
**TEGGE, JR. ET AL.**  
Serial No. 10/673,869  
Filing Date: **SEPTEMBER 29, 2003**

---

23. (Original) The method of Claim 22 wherein the at least one OR device of a given OR module provides a predetermined focal length range from among different focal length ranges for respective OR modules.

24. (Original) The method of Claim 22 wherein the at least one OR device comprises a fixed telescopic lens device.

25. (Original) The method of Claim 19 wherein the FSO communications device further comprises a base module connected to the AO module for providing relative movement between the base module and the OR module for optical beam aiming.

26. (Original) The method of Claim 25 wherein the base module comprises a base housing and at least one positioner carried thereby.

27. (Original) The method of Claim 26 wherein the base module further comprises a controller for controlling the at least one positioner and a remote control interface connected to the controller for permitting remote control of the at least one positioner.